

Rhodes Group

Documentation For Review

Doc Review Version: 1-B

02-25-2016

TABLE OF CONTENTS

CHAPTER 1 : Notes for Review Demo 1-B

CHAPTER 2 : Revised Table Definitions

FO_CDC_Outbound_Filter	4
FO_External_Form_Definition	6
FO_IF_Translations	7
FO_LabInfo	9

CHAPTER 3 : Glossary Notes and Examples

Glossary

CHAPTER 1 : Notes for Review Demo 1-B

These are notes to log what the review demo covers. Refer to specific TOC for contents.

Review Demo 1-B	02-25-2016
Format	PDF, Online and Word Docs links on Review Demo Home Page
Purpose	<ul style="list-style-type: none"> » Revisions to the Reference Manual table field name notes per phone mtg of 02-23-2016 » Revisions to glossary terms, they should match the table field names exactly » Fixes to glossary term display in online glossary, in online popups and in the PDF glossary. Did not change in the PDF footnotes to save room on the page.
Review Request Please provide comments.	<ul style="list-style-type: none"> » review table descriptions -- the content above the table listing » review table field name notes » review glossary term display; the line breaks should be working » log any additional terms to include in the new 'global' glossary » help identify any 'system-level' etc defaults as well as how the default works - ie "inserted in the record if field is blank when the order is saved" ... OR "Default used when the user-level value is not defined." etc. » items marked in yellow are particular questions or concerns » items marked in purple are things for me to do later

CHAPTER 2 : Revised Table Definitions

For review, revised table descriptions and field name notes for the following tables:

- >> "FO_CDC_Outbound_Filter" on page 4
- >> "FO_External_Form_Definition" on page 6
- >> "FO_IF_Translations" on page 7
- >> "FO_LabInfo" on page 9

Using this standard

Field	Type	Notes
TEMPLATE for Notes		WHAT / DEFN How to fill in field – Multi--- and/or Use this or that HOW Used / represents / calculates / evaluates / mask / etc Example via IE: or Allowed Values: Explanation of example
mrnumgenerationroutine	varchar(50)	Automatically generates an MRN number on the patient data screen. Use Rhodes recommended value. Typical value: ALPHA4NUMBER

Field	Type	Notes
blockmrlength	varchar(80)	<p>Multidimensional pipe delimited value¹, with leading and trailing pipes.</p> <p>Enter integers separated by pipes.</p> <p>Each number represents a MRN entry length that is NOT supported by the system.</p> <p>IE: 1 2 3 4 5 6 7 9 10 11 12 13 14 </p> <p>In this example, the MRN entry must be either 8 characters long or longer than 14 characters.</p>

¹Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

FO_CDC_Outbound_Filter

This table is used to specify which types of records would be valid outbound via the Client Data Concentrator Outbound interfaces (CDCOut). The filtering can be done for a specific qualifier or for a qualifier-client code combination.

Use table name in SQL statements as `FO_CDC_Outbound_Filter`

Field	Type	Notes
FilterID	int	ID field, a counter. Unique
MPIQualifier	varchar(50)	Enter a valid MPI qualifier code that accepts inbound messages; use only MPI qualifiers that have inbound interfaces so FAST can send out a message. To learn which MPI qualifier codes are valid here, look at FO_MPI_Qualifier.UseForCDCOutboundProcessing. If that field is set to 1, that MPI Qualifier code is valid to use here.
ClientCode	varchar(50)	Enter a valid client code or an asterisk (*) for all clients. If field is empty, default is all clients ?? . and does this field indicate which clients can use this function or anything like that??
SendOrder	bit	Bit field to determine if order messages are sent on CDCOutbound. Enter 0 or 1 0 = filter order messages, do not send 1 = send order messages
SendReceipt	bit	Bit field to determine if receipt order messages are sent on CDCOutbound. Enter 0 or 1 0 = filter receipt order messages, do not send 1 = send receipt order messages
SendCancel	bit	Bit field to determine if cancel order messages are sent on CDCOutbound. Enter 0 or 1 0 = filter cancel order messages, do not send 1 = send cancel order messages
SendNA	bit	Bit field to determine if SN/NA messages are sent on CDCOutbound. Enter 0 or 1 0 = filter SN/NA messages, do not send 1 = send SN/NA messages
OrderControl	varchar(2)	Order control code used with SENDNA option.

Field	Type	Notes
EditDate	datetime	Date record was edited. Informational
EditUser	varchar(50)	User who last edited record. Informational
CreateDate	datetime	Date record was created. Informational
CreateUser	varchar(50)	User who created record. Informational

FO_External_Form_Definition

Not required maintenance but is needed for embedding external reports using Microsoft SQL server reporting URL based pointers. (The external URLs made using SSRS reporting function.)

Use table name in SQL statements as FO_External_Form_Definition

Field	Type	Notes
ExternalForms_ID	bigint	ID field, a counter. Unique
ExternalFormCode	varchar(50)	Code to identify a single report. Enter a unique string as the code.
Description	varchar(255)	Enter a description for the report.
ReportURL	varchar(800)	URL that launches the report in the SSRS server. Enter a valid URL.
ReportType	varchar(50)	Code for the report type. Enter a string to identify the type. This code may be used as the type for other reports also.
CreateDate	datetime	Date record was created. Informational
EditDate	datetime	Date record was edited. Informational
CreateUser	varchar(50)	User who created the record. Informational
EditUser	varchar(50)	User who edited the record. Informational
FModule	varchar(50)	Swaps the default Rhodesformat for the SSRS form defined. Enter a valid FModule code to enable. Valid FModule Code: BATCHPROCESS
PermGroups	varchar(1000)	Determines which users can see a report based on permission group codes. Leave blank to make report available to all users. Multidimensional pipe delimited value ¹ , with leading and trailing pipes. Enter valid permission group codes separated by pipes.

¹Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

FO_IF_Translations

This table is used to specify translation values for external data arriving through the Client Data Concentrator interfaces (CDC).

Each record represents a particular field type of foreign and native values for an MPI qualifier and an Interface code. An interface code is assigned in the **config file of the comms** and processor jobs of an interface. **(does the system use the MPI-qual and Interface code COMBO? If so, should we say that it is a unique combo?)(So this FPValue would only use translation value in FAST where MPI-qual and Interface code combo matched the FAST record?)**

Use table name in SQL statements as FO_IF_Translations

Field	Type	Notes
FO_IF_Translations_ID	int	ID field, a counter. Unique
InterfaceCode	varchar (50)	Interface code for this translation. The interface code is defined in the Comms and Processor jobs config files. (need to expand 'Comms' to Communication or something else?)
TranslationType	varchar (50)	Enter a single character that represents a translation type. Allowed values: I = insurance C = client T = test code G = gender S = species M = marital P = provider B = bill to L = patient location R = relationship value PR = priority
ForeignValue	varchar (50)	Enter a value for this translation type in the external system.
FPValue	varchar (50)	Enter a value to translate to in FAST. For type I insurance translations, if the FPValue is "*DNU*" , then the system will not record any insurances from that message. The system will still force the bill to value if the above field is valued. (force it to what?) (and which above field?) This is only honored for the primary insurance (first IN1) segment in a message.
MPIQualifier	varchar (50)	MPI qualifier code. Enter a valid MPI qualifier code.
CreateDate	datetime	Date record was created. Informational

Field	Type	Notes
CreatedBy	varchar (50)	User who created the record. Informational
EditDate	datetime	Date record was edited. Informational
EditedBy	varchar (50)	User who last edited the record. Informational
ForceBillTo	Varchar (50)	<p>Defines the <code>billto</code> value for every order created by reference to this translation.</p> <p>Enter a valid FAST <code>billto</code> value. See Bill To table for valid entries of long code. [Insert link target_blank to Bill To table in the doc]</p> <p>Only applies to translation type I insurance for the first IN1 segment.</p> <p>This will override what was sent in the message or a default value for this MPI qualifier.</p> <p>This logic will be used only if the translation rules are activated to cause the system to translate the insurance code in the message.</p> <p>An IN1 segment must have at least an insurance code and a policy number to qualify as a valid segment. If it does not, no translation will be applied.</p>
ClientCode	varchar (50)	<p>Client code.</p> <p>Enter a valid client code.</p> <p>(is this a multidimensional pipe-delimited value?, I don't think so but just checking.)</p>

FO_LabInfo

This table contains a single row of values used to configure system functions.

Use table name in SQL statements as `FO_LabInfo`

Field	Type	Notes
LabInfo_ID	int	ID field, a counter. Unique
LabName	varchar (50)	Laboratory name for the login screen and reports
LabCode	varchar (20)	Code value for this lab.
LabAddress1	varchar (50)	Address field on reports .
LabAddress2	varchar (50)	Second address field on reports .
LabAddress3	varchar (50)	Third address field on reports.
LabAddress4	varchar (50)	Fourth address field on reports
LabDirector	varchar (50)	Name of lab director on reports.
Misc1	varchar (50)	Login screen user defined field #1.
Misc2	varchar (50)	Login screen user defined field #2.
Misc3	varchar (50)	Login screen user defined field #3.
Misc4	varchar (50)	Login screen user defined field #4.
Misc5	varchar (50)	Login screen user defined field #5.
UseVerify	int	Enter the integer 1 Do NOT change without Rhodes approval.
UseMandatorySteps	int	Enter the integer 1 Do NOT change without Rhodes approval.

Field	Type	Notes
Barcode_Security	decimal (18, 2)	Enter the real number 1.00 Do NOT change without Rhodes approval.
Barcode_Xunit	decimal (18, 2)	Enter the real number 150.00 Do NOT change without Rhodes approval.
Barcode_Yunit	decimal (18, 2)	Enter the real number 5.00 Do NOT change without Rhodes approval.
Def_PtLocCode	varchar (20)	System-level default patient location code on the order screen. Enter a valid patient location code. This code is only used if no value is in the field when the order is saved.
Def_Epi_Days	int	Enter the integer 30 Do NOT change without Rhodes approval.
Epi_Ins_Options	varchar (100)	Populates Insurance option drop-down list on the Episode Definition screen. Multidimensional pipe delimited value¹ , with leading and trailing pipes. Enter valid insurance codes separated by pipes. IE: INS1 INS2 INS3
Epi_BillTo_Options	varchar (100)	Populates Bill To option drop-down list on the Episode Definition screen. Multidimensional pipe delimited value² , with leading and trailing pipes. Enter valid billto codes separated by pipes. IE: P C

¹Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

²Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

Field	Type	Notes
SO_Review_Days	int	<p>System-level default number of days before a standing order expires and requires review.</p> <p>Enter an integer for the number of days.</p> <p>Used to calculate the number of days until standing order expiration.</p> <p>IE: 180</p> <p>(is this calculated from collection date, create date or ??)</p>
ResultSysURL	varchar (255)	<p>URL to connect to a client-provided lab result portal.</p> <p>Enter a valid URL.</p> <p>The URL may contain place holders for user name and password for the client-provided lab system.</p> <p>IE: HTTP://LabPortal.com /#USERNAME##/PASSWORD#</p>
BlockMRLength	varchar (80)	<p>Mask for MRN entry value.</p> <p>Multidimensional pipe delimited value¹, with leading and trailing pipes.</p> <p>Enter integers separated by pipes.</p> <p>Each number represents an MRN entry length that is NOT supported by the system.</p> <p>IE: 1 2 3 4 5 6 7 9 10 11 12 13 14 </p> <p>In this example, the MRN entry must be either 8 characters long or longer than 14 characters.</p>
ADT_Interface	varchar (255)	<p>Default value for the Outbound ADT system interface.</p> <p>Use Rhodes recommended value.</p>
OE_Interface	varchar (255)	<p>Default value for the Outbound OE system interface.</p> <p>Use Rhodes recommended value.</p>
Result_Interface	varchar (255)	<p>Default value for the Outbound RE system interface.</p> <p>Use Rhodes recommended value.</p>

¹Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

Field	Type	Notes
LogoImageFile	varchar (255)	The network path and file name for the logo file used on screen and report displays. Enter a valid network path and file name. The file must be a GIF or JPG image approximately 100x125 pixels. (for example: Images/reallyfinelogo.jpg ??) need leading or trailing slashes?
DefaultFacilityID	varchar (50)	System-level default facility ID code. Enter a valid facility ID code.
DefaultSpeciesCode	varchar (50)	Default species code. H = HUMAN
DefaultSpeciesName	varchar (50)	Default species name corresponding to the default species code. HUMAN
Def_ClientCode	varchar (50)	System-level default client ID code. Enter a valid client ID code.
DefOrdScreenReq	varchar (80)	System-level default requisition report name used when the REQ button on the order screen is clicked. Default used when the user-level value is not defined. Required value. Use Rhodes recommended value.
Callback_Callcode	varchar (50)	Value of "Call" for callback systems. Used when the Call button on the order screen phone definitions is clicked.
Callback_Faxcode	varchar (50)	Value of "Fax" for callback systems. Used when the Fax button on the order screen phone definitions is clicked.
MRNumGenerationRoutine	varchar (50)	Automatically generates an MRN number on the patient data screen. Use Rhodes recommended value. Typical value: ALPHA4NUMBER4
PasswordExpirationDays	int	Number of days before a user password expires and must be reset. Enter an integer for the number of days.

Field	Type	Notes
Def_AreaCode	varchar (50)	System-level default for area code. Enter an integer for a valid area code. Used on the patient demographic screen if area code is not provided. (when is it used on the screen -- at the time the user is working on the order or after the fact inserted into the record when the order is saved?)
AutoOrderCodeWhenCCDoc	varchar (50)	Used to order tests automatically when copy to physician is used on the order screen. Multidimensional pipe delimited value ¹ , with leading and trailing pipes. Enter valid order test codes separated by pipes.
MRNumMask	varchar (50)	Medical record number mask used to validate the MRN field on the order screen. Enter “#” to represent numbers and “@” to represent alpha characters. Typical setting: @@@@#####
CallToOrderCode	varchar (50)	Used in the mini window for call/fax to automatically order a test code when the Call button is clicked on the order screen. Use a valid order code. (valid order code or valid order test code or valid test code, what is the difference?)
FaxToOrderCode	varchar (50)	Used in the mini window for call/fax to automatically order a test code when the Fax button is clicked on the order screen. Enter a valid order code. (valid order code or valid order test code or valid test code, what is the difference?)
FastingOrderCode	varchar (50)	Used to automatically order a test if the fasting priority is selected at the order level on the order screen. The rule is activated at the time the Verify button is clicked. Enter a valid order test code. (valid order code or valid order test code or valid test code, what is the difference?)

¹Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

Field	Type	Notes
PastOrderDays	int	<p>Number of days back that the system will allow a user to date a new order.</p> <p>Enter an integer for the number of days.</p> <p>The collection date is evaluated and if the order is too old, a warning message will be displayed.</p>
FutureOrderDays	int	<p>Number of days in the future that the system will allow a user to date a new order.</p> <p>Enter an integer for the number of days.</p> <p>The collection date is evaluated and if the order is too far in the future, a warning message will be displayed.</p>
ReqID_Mask	varchar (50)	<p>Mask used to validate the requisition ID on the order screen.</p> <p>Enter “#” to represent numbers and “@” to represent alpha characters.</p> <p>Typical setting: #####</p> <p>This setting requires an 8 character numeric only entry.</p>
ReqID_Exclude_Characters	varchar (80)	<p>Defines the characters to exclude from the requisition ID value.</p> <p>Multidimensional COMMA delimited value.</p> <p>Enter the characters, separated by commas, that should be excluded from the requisition ID value on the order screen.</p>
ReqID_Length_Range	varchar (50)	<p>Represents the minimum and maximum number of characters allowed in the requisition ID field on the order screen.</p> <p>Enter two integers separated by a dash.</p> <p>Do not enter a value here if an edit mask is defined for the requisition ID field.</p> <p>If the value is set as '10-15', then an entry between 10 and 15 characters long is allowed.</p>
DefaultPerformingLab	varchar (50)	<p>System-level default performing lab code value.</p> <p>Enter a valid performing lab code value.</p> <p>Used to supply a performing lab code to the system when one is required and not provided by rules.</p>

Field	Type	Notes
DefaultBatchDestination	varchar (50)	System-level default batch destination code. Enter a valid batch destination code. Used if not provided by rules for transport logic.
AccessionFormat	varchar (50)	Drives the routines that create unique FASTac- cessions and container IDs. Use Rhodes recommended value. Allowed values: ENTRYGROUPCODE = use entry group code to derive format. 7SEQ = create a 7 character unique number 8SEQ = create a 8 character unique number 9SEQ = create a 9 character unique number 10SEQ = create a 10 character unique number 11SEQ = create a 11 character unique number 12SEQ = create a 12 character unique number
TestCompDupExcludeDept	varchar (50)	Defines the department codes to exclude from the test overlap/duplication logic during order entry. Multidimensional pipe delimited value ¹ , with lead- ing and trailing pipes. Enter valid department codes separated by pipes. This value is used to exclude the list of department codes it represents from applying to the test over- lap/duplication logic during order entry. Any department codes in this list will not be evaluated for test overlap. IE: BB MC CY PATH If this field is blank, the system will default to MC BB CY and will exclude those departments from test overlap/duplication logic.

¹Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

Field	Type	Notes
DisplayBDEFIELDS	varchar (50)	<p>Determines which fields to display in the blind duplicate entry screen.</p> <p>Multidimensional pipe delimited value¹, with leading and trailing pipes.</p> <p>Enter allowed values shown below separated by pipes.</p> <p>The default value of ALL may be used to display all fields.</p> <p>If this field is blank, the system will default to ALL .</p> <p>Allowed values:</p> <p>M = MRN</p> <p>N = patient name</p> <p>D = DOB</p> <p>S = gender</p> <p>T = telephone</p> <p>C = client</p> <p>L = location</p> <p>P = physician</p> <p>E = test related fields</p> <p>CC1 = copy to 1</p> <p>CC2 = copy to 2</p> <p>CC3 = copy to 3</p> <p>CC4 = copy to 4</p> <p>ADD = address fields</p>

¹Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

Field	Type	Notes
TestCompDupExcludeTests	varchar (500)	<p>Defines the order codes to exclude from the test overlap/duplication logic during order entry.</p> <p>Multidimensional pipe delimited value¹, with leading and trailing pipes.</p> <p>Enter valid order codes separated by pipes.</p> <p>This value is used to exclude the list of order codes it represents from applying to the test overlap/duplication logic during order entry.</p> <p>Any order codes in this list will not be evaluated for test overlap.</p>
SalesTaxUserLoc	varchar (100)	<p>Defines the user locations and their corresponding sales tax to be used for price calculations on the payments screen.</p> <p>Multidimensional pipe delimited value², with leading and trailing pipes.</p> <p>Enter valid user location code - sales tax percent pairs separated pipes.</p> <p>Each value in a pair is separated by a dash.</p> <p>IE: USERLOC1-6.5 USERLOC2-6 </p>
LabAccessionAlphaCharacters	varchar (50)	<p>Represents the letters used in the lab accession generation when FAST will pre-generate it and send it to the LIS.</p> <p>Multidimensional pipe delimited value³, with leading and trailing pipes.</p> <p>Enter single capital letters separated by pipes.</p> <p>IE: A Q Z </p>
LabAccessionFormat	varchar (50)	<p>Defines format for creation of lab accession values.</p> <p>Use Rhodes recommended value.</p> <p>IE: 1A,8N</p> <p>The format '1A,8N' generates lab accessions that are one alpha character followed by 8 numeric characters.</p>

¹Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

²Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

³Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

Field	Type	Notes
PaymentTypes	varchar (100)	<p>Populates the payment type drop-down on the payment screen.</p> <p>Multidimensional pipe delimited value¹, with leading and trailing pipes.</p> <p>Enter valid payment type codes separated by pipes. IE: CARD CHECK CASH </p>
PaymentCardTypes	varchar (100)	<p>Populates the credit type drop-down on the payment screen.</p> <p>Multidimensional pipe delimited value², with leading and trailing pipes.</p> <p>Enter valid credit card type codes separated by pipes. IE: AMEX VISA DINNERS DEBIT </p>
AutoCCORDCode	varchar (50)	<p>Default test code for the ordering physician when the rule is activated to order a test battery to hold the values of ordering and copy to codes.</p> <p>The system will automatically enter the physician code for the order if the answer test code matches this value.</p> <p>Enter a valid test code.</p> <p>Used to send the ordering / copy to physician values to a client as a test code in a lab report.</p>
AutoCCccCode	varchar (50)	<p>Default test code for copy to physician when the rule is activated to order a test battery to hold the values of ordering and copy to codes.</p> <p>The system will automatically enter the copy to codes for the order if the answer test code matches this value.</p> <p>Enter a valid test code.</p>

¹Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

²Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

Field	Type	Notes
CollectionLocations	varchar (500)	<p>System-level default for collection location if not defined at the user level.</p> <p>Enter a valid collection location.</p> <p>Used to evaluate the collection location entered on the order screen.</p> <p>(does this 'evaluate' mean that the field will be filled in with this value if the field is blank when the record is saved? or what?)</p>
CDCOrderEvalHours	int	<p>Represents a number of hours.</p> <p>Enter an integer for the number of hours.</p> <p>Default is 0.</p> <p>Used to validate the collection date/time on the order screen when a previously created order is opened.</p> <p>If the order collection date/time is older than this value, the collection date/time field is cleared to allow the user to enter a new one.</p>
PtRaceEntries	varchar (255)	<p>Populates the race drop-down on the patient demographics screen.</p> <p>Multidimensional pipe delimited value¹, with leading and trailing pipes.</p> <p>Enter valid race codes separated by pipes.</p>
PtEthnicityEntries	varchar (255)	<p>Populates the ethnicity drop-down on the patient demographics screen.</p> <p>Multidimensional pipe delimited value², with leading and trailing pipes.</p> <p>Enter valid ethnicity codes separated by pipes.</p>
FutureOrderSecsAutoReceive	int	<p>Represents a number of seconds.</p> <p>Enter an integer for the number of seconds.</p> <p>If the collection date/time is in the future by more than this number of seconds, the accession is excluded from auto receive processes.</p>

¹Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

²Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

Field	Type	Notes
FutureOrderSecsNotTriggerLabels	int	Represents a number of seconds. Enter an integer for the number of seconds. If the collection date/time is in the future by more than this number of seconds, no label is produced.
CID_Prefix	varchar (50)	Prefix characters for ContainerID. Enter the character string to use as the prefix for ContainerIDs.
ExceptionExecFolder	varchar (255)	Pathway for CSTools installation. Enter a valid network path. (does this need leading or trailing slashes or need drive name etc?)
ExceptionExecutable	varchar (80)	File name for CSTools executable. Include ".exe" in the file name. (need or specifically do not include any slashes?)
OrderActionPhoneNumbers	varchar (255)	Designed for use in TEST area. Multidimensional pipe delimited value¹ , with leading and trailing pipes. Enter phone numbers, separated by pipes, to limit user's choice of entry. (what is the format for the phone numbers? include dashes, parenthesis, etc?) and are these phone numbers then the only phone numbers that the user can enter, do they populate a drop-down or anything?
RecognizedPrefixes	varchar (255)	Defines the prefixes to remove from patient last name in patient matching rules. Storage of prefixes depends on permission. Multidimensional pipe delimited value² , with leading and trailing pipes. Enter patient last name prefixes that should be removed from patient last names via matching rules. Enter prefixes separated by pipes.

¹Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

²Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

Field	Type	Notes
RecognizedSuffixes	varchar (255)	<p>Defines the suffixes to remove from patient last name in patient matching rules.</p> <p>Storage of suffixes depends on permission.</p> <p>Multidimensional pipe delimited value¹, with leading and trailing pipes.</p> <p>Enter patient last name suffixes that should be removed from patient last names via matching rules.</p> <p>Enter suffixes separated by pipes.</p>
OrderCollectLocationTypes	varchar (255)	<p>Populates the collection (location?) type drop-down on the patient collection location screen.</p> <p>Multidimensional pipe delimited value², with leading and trailing pipes.</p> <p>Enter valid collection (location?) type codes separated by pipes.</p>
SendOrderForFPCancelToLIS	bit	<p>Bit flag to indicate if FAST should trigger a new order message before a cancel message when sending cancellation to LIS.</p> <p>This would only be true for orders that have not been previously sent to the LIS or have originated in LIS.</p> <p>The system will evaluate both of these conditions by checking to see if the <code>IFTriggerUpdate</code> field has been filled at the test level.</p> <p>Enter 0 or 1</p> <p>0 = do not trigger NW order before cancel</p> <p>1 = trigger NW Order before sending cancel</p>
TriggerCancelCDCOutbound	bit	<p>Bit flag to indicate if FAST should trigger cancellation messages to the outbound CDC interface for orders where <code>FO_Accessions.Origin</code> equals 'C' or 'T'.</p> <p>Enter 0 or 1</p> <p>0 = do not trigger cancellation messages to outbound CDC</p> <p>1 = trigger cancellation messages to outbound CDC</p>

¹Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

²Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

Field	Type	Notes
TDC_In_Interfaces	varchar (255)	Interface code for Trusted Data Concentrator inbound interface Code is written to the interface code field when a trigger row is written by FAST. It must match what is expected for interface to function.
TDC_Out_Interfaces	varchar (255)	Interface code for Trusted Data Concentrator outbound interface. Code is written to the interface code field when a trigger row is written by FAST. It must match what is expected for interface to function.
CDC_In_Interfaces	varchar (255)	Interface code for Client Data Concentrator inbound interface. Code is written to the interface code field when a trigger row is written by FAST. It must match what is expected for interface to function.
CDC_Out_Interfaces	varchar (255)	Interface code for Client Data Concentrator outbound interface. Code is written to the interface code field when a trigger row is written by FAST. It must match what is expected for interface to function.
CDC_OUT_Cancel_Order_Control	varchar (50)	Cancellation order control to be used in FO_IF_Trigger_CDCOutbound. OrderControl when FAST writes a cancellation trigger. Enter OC or CA Code is written to the trigger table when a trigger row is written by FAST.
RecentPatientSearchType	varchar (50)	Default RECENT PTS search type. Enter an allowed value. Allowed values: USERLOCATION ENTRYGROUPCODE PTACCESSGROUP MPI

Field	Type	Notes
RecentPatientSearchDays	varchar (50)	Default number of days to evaluate for recent activity. Enter an integer for the number of days. Used with RECENT PTS search option. Based on edit date not create date.
UseInterfaceTriggerService	bit	Bit flag to indicate if FAST should enable FAST Interface Trigger Layer. Used in conjunction with FAST Interface Trigger Process Service. Enter 0 or 1 0 = do not use trigger layer (FAST will continue to write to trigger table) 1 = use FAST Interface Trigger Layer and FAST Interface Trigger Process Service (started configured and separately) (A background service for creating application to interface subsystem triggers. When this is set the application writes general triggers for the background job to process in the table FO_IF_AppTrigger_Queue. The background job then creates the explicit table updates and the triggering to the FO_ID_Trigger table.)
ProvCodesTriggerFreeText	varchar (255)	Defines provider codes for which a freetext provider name is allowed. Multidimensional pipe delimited value ¹ , with leading and trailing pipes. Enter valid provider codes separated by pipes.
UseClientDrivenOrderScreen	bit	Bit flag to indicate if client-driven order screen is default order screen. Enter 0 or 1 0 = use original FAST order screen 1 = use client-driven order screen

¹Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

Field	Type	Notes
UnknownCollectDate	date	Date sent to LIS when Unknown Collection box is checked. Enter collect date as MM/DD/YYYY format.
UnknownCollectTime	varchar (50)	Time sent to LIS when Unknown Collection box is checked. Enter collect time as HH:MM 24-hour format.
SpecimenPresentsDefTechCode	varchar (50)	Default tech code for collection tech in the Specimen Presents mode. Enter a valid tech code.
MaxOrderCopyToProvs	varchar (50)	Defines the maximum number of 'Copy To' providers allowed per order. Enter an integer from 0 to 10.
FPToRREInterfaceCode	varchar (50)	Interface code for the Fast to RRE interface service. Enter a valid interface code.
LabRegionCode	varchar (50)	Connects a lab code to a larger organization charting process. Enter a valid region code as defined in an organizations chart.
LabDivisionCode	varchar (50)	Connects a lab code to a larger organization charting process. Enter a valid division code as defined in an organizations chart.
LabSubDivisionCode	varchar (50)	Connects a lab code to a larger organization charting process. Enter a valid sub-division code as defined in an organizations chart.
DefaultFeeSchedule	varchar (80)	Default fee schedule for multiple fee schedule implementations. (are there any allowed values here, what should be entered?)
DefaultFeeScheduleOption	varchar (80)	Default option in the default fee schedule for multiple fee schedule implementations. (are there any allowed values here, what should be entered?)

Field	Type	Notes
WorkflowMethods	varchar (255)	<p>Workflow methods used by the site.</p> <p>Populates the workflow method drop-down on the integrated search page.</p> <p>Multidimensional pipe delimited value¹, with leading and trailing pipes.</p> <p>Enter one or more allowed values separated by pipes.</p> <p>Allowed values:</p> <p>PATIENT PRESENTS</p> <p>SPECIMEN PRESENTS</p> <p>INDUSTRIAL TOX</p>
DefaultWorkflowMethod	varchar (50)	<p>System-level default workflow.</p> <p>Overridden by a user location or user-defined default workflow.</p> <p>Enter an allowed value.</p> <p>Allowed values:</p> <p>PATIENT PRESENTS</p> <p>SPECIMEN PRESENTS</p> <p>INDUSTRIAL TOX</p>
ITOXDefProviderCode	varchar (50)	<p>Default provider code for orders placed while in ITOX workflow.</p> <p>Enter a valid provider code.</p>
ITOXDefCDCCodeq	varchar (50)	<p>Default diagnosis code for orders placed while in ITOX workflow.</p> <p>Enter a valid diagnosis code.</p>
PatientFeeSchedule	varchar (80)	<p>Default fee schedule code applied to FAST accessions labeled with a <code>billto</code> value of 'Patient/Guarantor'.</p> <p>Enter a valid fee schedule code.</p> <p>(are there any allowed values here, what should be entered?)</p>

¹Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

Field	Type	Notes
PatientFeeScheduleOption	varchar (80)	Default fee schedule option applied to FAST accessions labeled with a billto value of 'Patient/Guarantor'. Enter valid fee schedule option. (are there any allowed values here, what should be entered?)
CashFeeSchedule	varchar (80)	Default fee schedule code applied to FAST accessions labeled as 'Bill to Cash'. Enter a valid fee schedule code. (are there any allowed values here, what should be entered?)
CashFeeScheduleOption	varchar (80)	Default fee schedule option applied to FAST accessions labeled as 'Bill to Cash'. Enter a valid fee schedule option. (are there any allowed values here, what should be entered?)
PaymentReceiptExternalFormCode	varchar (50)	The form code from FO_External_Form_Definition. ExternalFormCode that can be used to show a user-customized SSRS-based payment receipt form.
PtDefaultDOB	date	Default DOB. Enter DOB as MM/DD/YYYY format.
BatchListRPTEExternalFormCode	varchar (50)	The form code from FO_External_Form_Definition. ExternalFormCode that can be used to show a user-customized SSRS-based Batch List form. Leave blank to use the default report.
DispatchListRPTEExternalFormCode	varchar (50)	The external form code for the dispatch list user custom report. (what should be entered here? something the user makes up or a code from somewhere else?)

CHAPTER 3 : Glossary Notes and Examples

Consolidated field names that occur in multiple tables into a 'global' glossary.

Those field names are marked as [Various Tables].

(Did not use [All Tables] because not sure if that is accurate - is it?)

They also still appear in the glossary for the table (as tablename.fieldname) but only appear once alphabetically in the glossary. They are marked as [Various tables]

For example **CreateDate [Various Tables]**¹ is in the glossary. This term style will not match any content written as CreateDate, but will be available for a search and in the alphabetically listing of the glossary.

Also included in the global glossary is the term -- **Multidimensional pipe delimited value**².

This term is in the glossary so we can provide a more extensive explanation of how to use it.

Example:

The term FO_LabInfo.epi_billto_options will be in the content and display as a glossary term.

When a reader either uses search or simply looks in the glossary, they will be able to find the term alphabetically as either just epi_billto_options or FO_LabInfo.epi_billto_options.

Same for **FO_CDC_Outbound_Filter.ClientCode**³ term.

¹Date record was created. Informational

²Method which allows entry of multiple values in a field. Values are separated by the pipe character -- | In addition a leading, or starting, and trailing, or ending pipe is required. For example the string |A|B|C|D| provides the values A, B, C and D to the system.

³Enter a valid client code or an asterisk (*) for all clients. If field is empty, default is all clients.

A

AccessionFormat [FO_LabInfo]

Drives the routines that create unique FAST accessions and container IDs.

Use Rhodes recommended value.

Allowed Values:

ENTRYGROUPCODE = use entry group code to derive format.

7SEQ = create a 7 character unique number

8SEQ = create a 8 character unique number

9SEQ = create a 9 character unique number

10SEQ = create a 10 character unique number

11SEQ = create a 11 character unique number

12SEQ = create a 12 character unique number

ADT_Interface [FO_LabInfo]

Default value for the Outbound ADT system interface.

Use Rhodes recommended value.

AutoCCccCode [FO_LabInfo]

Default test code for copy to physician when the rule is activated to order a test battery to hold the values of ordering and copy to codes.

The system will automatically enter the copy to codes for the order if the answer test code matches this value.

Enter a valid test code.

AutoCCORDCode [FO_LabInfo]

Default test code for the ordering physician when the rule is activated to order a test battery to hold the values of ordering and copy to codes.

The system will automatically enter the physician code for the order if the answer test code matches this value.

Enter a valid test code.

Used to send the ordering / copy to physician values to a client as a test code in a lab report.

AutoOrderCodeWhenCCDoc [FO_LabInfo]

Used to order tests automatically when copy to physician is used on the order screen.

Multidimensional pipe delimited value, with leading and trailing pipes.

Enter valid order test codes separated by pipes.

B

Barcode_Security [FO_LabInfo]

Enter the real number 1.00
Do NOT change without Rhodes approval.

Barcode_Xunit [FO_LabInfo]

Enter the real number 150.00
Do NOT change without Rhodes approval.

Barcode_Yunit [FO_LabInfo]

Enter the real number 5.00
Do NOT change without Rhodes approval.

BatchListRPTEExternalFormCode [FO_LabInfo]

The form code from FO_External_Form_Definition.
ExternalFormCode that can be used to show a user-customized SSRS-based Batch List form.
Leave blank to use the default report.

BlockMRLength [FO_LabInfo]

Mask for MRN entry value.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter integers separated by pipes.
Each number represents an MRN entry length that is NOT supported by the system.
IE: |1|2|3|4|5|6|7|9|10|11|12|13|14|
In this example, the MRN entry must be either 8 characters long or longer than 14 characters.

C

Callback_Callcode [FO_LabInfo]

Value of "Call" for callback systems.
Used when the Call button on the order screen phone definitions is clicked.

Callback_Faxcode [FO_LabInfo]

Value of "Fax" for callback systems.

Used when the Fax button on the order screen phone definitions is clicked.

CallToOrderCode [FO_LabInfo]

Used in the mini window for call/fax to automatically order a test code when the Call button is clicked on the order screen.

Enter a valid order code.

CashFeeSchedule [FO_LabInfo]

Default fee schedule code applied to FAST accessions labeled as 'Bill to Cash'.

Enter a valid fee schedule code.

CashFeeScheduleOption [FO_LabInfo]

Default fee schedule option applied to FAST accessions labeled as 'Bill to Cash'.

Enter a valid fee schedule option.

CDC_In_Interfaces [FO_LabInfo]

Interface code for Client Data Concentrator inbound interface.

Code is written to the interface code field when a trigger row is written by FAST. It must match what is expected for interface to function.

CDC_OUT_Cancel_Order_Control [FO_LabInfo]

Cancellation order control to be used in FO_IF_Trigger_CDCOutbound.

OrderControl when FAST writes a cancellation trigger.

Enter OC or CA

Code is written to the trigger table when a trigger row is written by FAST.

CDC_Out_Interfaces [FO_LabInfo]

Interface code for Client Data Concentrator outbound interface.

Code is written to the interface code field when a trigger row is written by FAST. It must match what is expected for interface to function.

CDCOrderEvalHours [FO_LabInfo]

Represents a number of hours.

Enter an integer for the number of hours.

Default is 0.

Used to validate the collection date/time on the order screen when a previously created order is opened.

If the order collection date/time is older than this value, the collection date/time field is cleared to allow the user to enter a new one.

CID_Prefix [FO_LabInfo]

Prefix characters for ContainerID.

Enter the character string to use as the prefix for ContainerIDs.

ClientCode [FO_CDC_Outbound_Filter]

Enter a valid client code or an asterisk (*) for all clients.

If field is empty, default is all clients.

ClientCode [FO_IF_Translations]

Client code.

Enter a valid client code.

CollectionLocations [FO_LabInfo]

System-level default for collection location if not defined at the user level.

Enter a valid collection location.

Used to evaluate the collection location entered on the order screen.

CreateDate [FO_CDC_Outbound_Filter]

Date record was created. Informational

CreateDate [FO_External_Form_Definition]

Date record was created. Informational

CreateDate [FO_IF_Translations]

Date record was created. Informational

CreateDate [Various Tables]

Date record was created. Informational

CreatedBy [FO_IF_Translations]

User who created the record. Informational

CreatedBy [Various Tables]

User who created the record. Informational

CreateUser [FO_CDC_Outbound_Filter]

User who created record. Informational

CreateUser [FO_External_Form_Definition]

User who created the record. Informational

CreateUser [Various Tables]

User who created record. Informational

D

Def_AreaCode [FO_LabInfo]

System-level default for area code.

Enter an integer for a valid area code.

Used on the patient demographic screen if area code is not provided.

Def_ClientCode [FO_LabInfo]

System-level default client ID code.

Enter a valid client ID code.

Def_Epi_Days [FO_LabInfo]

Enter the integer 30

Do NOT change without Rhodes approval.

Def_PtLocCode [FO_LabInfo]

System-level default patient location code on the order screen.
Enter a valid patient location code.
This code is only used if no value is in the field when the order is saved.

DefaultBatchDestination [FO_LabInfo]

System-level default batch destination code.
Enter a valid batch destination code.
Used if not provided by rules for transport logic.

DefaultFacilityID [FO_LabInfo]

System-level default facility ID code.
Enter a valid facility ID code.

DefaultFeeSchedule [FO_LabInfo]

Default fee schedule for multiple fee schedule implementations.

DefaultFeeScheduleOption [FO_LabInfo]

Default option in the default fee schedule for multiple fee schedule implementations.

DefaultPerformingLab [FO_LabInfo]

System-level default performing lab code value.
Enter a valid performing lab code value.
Used to supply a performing lab code to the system when one is required and not provided by rules.

DefaultSpeciesCode [FO_LabInfo]

Default species code.
H = HUMAN

DefaultSpeciesName [FO_LabInfo]

Default species name corresponding to the default species code.
HUMAN

DefaultWorkflowMethod [FO_LabInfo]

System default workflow.
Overridden by a user location or user-defined default workflow.
Enter an allowed value.
Allowed values:
PATIENT PRESENTS
SPECIMEN PRESENTS
INDUSTRIAL TOX

DefOrdScreenReq [FO_LabInfo]

System-level default requisition report name used when the REQ button on the order screen is clicked.
Default used when the user-level value is not defined.
Required value.
Use Rhodes recommended value.

Description [FO_External_Form_Definition]

Enter a description for the report.

DispatchListRPTEExternalFormCode [FO_LabInfo]

The external form code for the dispatch list user custom report.

DisplayBDEFields [FO_LabInfo]

Determines which fields to display in the blind duplicate entry screen.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter allowed values shown below separated by pipes.
The default value of |ALL| may be used to display all fields.
If this field is blank, the system will default to |ALL|.
Allowed values:
M = MRN
N = patient name
D = DOB
S = gender
T = telephone
C = client
L = location
P = physician

E = test related fields
CC1 = copy to 1
CC2 = copy to 2
CC3 = copy to 3
CC4 = copy to 4
ADD = address fields

E

EditDate [FO_CDC_Outbound_Filter]

Date record was edited. Informational

EditDate [FO_External_Form_Definition]

Date record was edited. Informational

EditDate [FO_IF_Translations]

Date record was edited. Informational

EditDate [Various Tables]

Date record was edited. Informational

EditedBy [FO_IF_Translations]

User who last edited the record. Informational

EditedBy [Various Tables]

User who last edited the record. Informational

EditUser [FO_CDC_Outbound_Filter]

User who last edited record. Informational

EditUser [FO_External_Form_Definition]

User who edited the record. Informational

EditUser [Various Tables]

User who last edited record. Informational

Epi_BillTo_Options [FO_LabInfo]

Populates Bill To option drop-down list on the Episode Definition screen.

Multidimensional pipe delimited value, with leading and trailing pipes.

Enter valid billto codes separated by pipes.

IE: |P|C||

Epi_Ins_Options [FO_LabInfo]

Populates Insurance option drop-down list on the Episode Definition screen.

Multidimensional pipe delimited value, with leading and trailing pipes.

Enter valid insurance codes separated by pipes.

IE: |INS1|INS2|INS3|

ExceptionExecFolder [FO_LabInfo]

Pathway for CSTools installation.

Enter a valid network path.

ExceptionExecutable [FO_LabInfo]

File name for CSTools executable.

Include ".exe" in the file name.

ExternalFormCode [FO_External_Form_Definition]

Code to identify a single report.

Enter a unique string as the code.

ExternalForms_ID [FO_External_Form_Definition]

ID field, a counter. Unique

F

FastingOrderCode [FO_LabInfo]

Used to automatically order a test if the fasting priority is selected at the order level on the order screen. The rule is activated at the time the Verify button is clicked.

Enter a valid order test code.

FaxToOrderCode [FO_LabInfo]

Used in the mini window for call/fax to automatically order a test code when the Fax button is clicked on the order screen.

Enter a valid order code.

FilterID [FO_CDC_Outbound_Filter]

ID field, a counter. Unique

FO_CDC_Outbound_Filter.ClientCode

Enter a valid client code or an asterisk (*) for all clients.

If field is empty, default is all clients.

FO_CDC_Outbound_Filter.CreateDate

Date record was created. Informational

FO_CDC_Outbound_Filter.CreateUser

User who created record. Informational

FO_CDC_Outbound_Filter.EditDate

Date record was edited. Informational

FO_CDC_Outbound_Filter.EditUser

User who last edited record. Informational

FO_CDC_Outbound_Filter.FilterID

ID field, a counter. Unique

FO_CDC_Outbound_Filter.MPIQualifier

Enter a valid MPI qualifier code that accepts inbound messages; use only MPI qualifiers that have inbound interfaces so FAST can send out a message.

To learn which MPI qualifier codes are valid here, look at FO_MPI_Qualifier.UseForCDCOutboundProcessing. If that field is set to 1, that MPI Qualifier code is valid to use here.

FO_CDC_Outbound_Filter.OrderControl

Order control code used with SENDNA option.

FO_CDC_Outbound_Filter.SendCancel

Bit field to determine if cancel order messages are sent on CDCOutbound.

Enter 0 or 1

0 = filter cancel order messages, do not send

1 = send cancel order messages

FO_CDC_Outbound_Filter.SendNA

Bit field to determine if SN/NA messages are sent on CDCOutbound.

Enter 0 or 1

0 = filter SN/NA messages, do not send

1 = send SN/NA messages

FO_CDC_Outbound_Filter.SendOrder

Bit field to determine if order messages are sent on CDCOutbound.

Enter 0 or 1

0 = filter order messages, do not send

1 = send order messages

FO_CDC_Outbound_Filter.SendReceipt

Bit field to determine if receipt order messages are sent on CDCOutbound.

Enter 0 or 1

0 = filter receipt order messages, do not send

1 = send receipt order messages

FO_External_Form_Definition.CreateDate

Date record was created. Informational

FO_External_Form_Definition.CreateUser

User who created the record. Informational

FO_External_Form_Definition.Description

Enter a description for the report.

FO_External_Form_Definition.EditDate

Date record was edited. Informational

FO_External_Form_Definition.EditUser

User who edited the record. Informational

FO_External_Form_Definition.ExternalFormCode

Code to identify a single report.
Enter a unique string as the code.

FO_External_Form_Definition.ExternalForms_ID

ID field, a counter. Unique

FO_External_Form_Definition.FPModule

Swaps the default Rhodes format for the SSRS form defined.
Enter a valid FPModule code to enable.
Valid FPModule Code:
BATCHPROCESS

FO_External_Form_Definition.PermGroups

Determines which users can see a report based on permission group codes.
Leave blank to make report available to all users.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter valid permission group codes separated by pipes.

FO_External_Form_Definition.ReportType

Code for the report type.

Enter a string to identify the type. This code may be used as the type for other reports also.

FO_External_Form_Definition.ReportURL

URL that launches the report in the SSRS server.

Enter a valid URL.

FO_IF_Translations.ClientCode

Client code.

Enter a valid client code.

FO_IF_Translations.CreateDate

Date record was created. Informational

FO_IF_Translations.CreatedBy

User who created the record. Informational

FO_IF_Translations.EditDate

Date record was edited. Informational

FO_IF_Translations.EditedBy

User who last edited the record. Informational

FO_IF_Translations.FO_IF_Translations_ID

ID field, a counter. Unique

FO_IF_Translations.ForceBillTo

Defines the billto value for every order created by reference to this translation.

Enter a valid FAST billto value. See Bill To table for valid entries of long code.

Only applies to translation type I insurance for the first IN1 segment.

This will override what was sent in the message or a default value for this MPI qualifier.

This logic will be used only if the translation rules are activated to cause the system to translate the insurance code in the message.

An IN1 segment must have at least an insurance code and a policy number to qualify as a valid segment. If it does not, no translation will be applied.

FO_IF_Translations.ForeignValue

Enter a value for this translation type in the external system.

FO_IF_Translations.FPValue

Enter a value to translate to in FAST.

For type I insurance translations, if the FPValue is "**DNU**", then the system will not record any insurances from that message.

The system will still force the billto value if the above field is valued.

This is only honored for the primary insurance (first IN1) segment in a message.

FO_IF_Translations.InterfaceCode

Interface code for this translation. The interface code is defined in the Comms and Processor jobs config files.

FO_IF_Translations.MPIQualifier

MPI qualifier code.

Enter a valid MPI qualifier code.

FO_IF_Translations.TranslationType

Enter a single character that represents a translation type.

Allowed values:

I = insurance

P = provider

C = client

B = bill to

T = test code

L = patient location

G = gender

R = relationship value

S = species

PR = priority
M = marital

FO_IF_Translations_ID [FO_IF_Translations]

ID field, a counter. Unique

FO_LabInfo.AccessionFormat

Drives the routines that create unique FAST accessions and container IDs.
Use Rhodes recommended value.

Allowed Values:

ENTRYGROUPCODE = use entry group code to derive format.

7SEQ = create a 7 character unique number

8SEQ = create a 8 character unique number

9SEQ = create a 9 character unique number

10SEQ = create a 10 character unique number

11SEQ = create a 11 character unique number

12SEQ = create a 12 character unique number

FO_LabInfo.ADT_Interface

Default value for the Outbound ADT system interface.
Use Rhodes recommended value.

FO_LabInfo.AutoCCccCode

Default test code for copy to physician when the rule is activated to order a test battery to hold the values of ordering and copy to codes.

The system will automatically enter the copy to codes for the order if the answer test code matches this value.

Enter a valid test code.

FO_LabInfo.AutoCCORDCode

Default test code for the ordering physician when the rule is activated to order a test battery to hold the values of ordering and copy to codes.

The system will automatically enter the physician code for the order if the answer test code matches this value.

Enter a valid test code.

Used to send the ordering / copy to physician values to a client as a test code in a lab report.

FO_LabInfo.AutoOrderCodeWhenCCDoc

Used to order tests automatically when copy to physician is used on the order screen.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter valid order test codes separated by pipes.

FO_LabInfo.Barcode_Security

Enter the real number 1.00
Do NOT change without Rhodes approval.

FO_LabInfo.Barcode_Xunit

Enter the real number 150.00
Do NOT change without Rhodes approval.

FO_LabInfo.Barcode_Yunit

Enter the real number 5.00
Do NOT change without Rhodes approval.

FO_LabInfo.BatchListRPTEExternalFormCode

The form code from FO_External_Form_Definition.
ExternalFormCode that can be used to show a user-customized SSRS-based Batch List form.
Leave blank to use the default report.

FO_LabInfo.BlockMRLength

Mask for MRN entry value.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter integers separated by pipes.
Each number represents an MRN entry length that is NOT supported by the system.
IE: |1|2|3|4|5|6|7|9|10|11|12|13|14|
In this example, the MRN entry must be either 8 characters long or longer than 14 characters.

FO_LabInfo.Callback_Callcode

Value of "Call" for callback systems.
Used when the Call button on the order screen phone definitions is clicked.

FO_LabInfo.Callback_Faxcode

Value of "Fax" for callback systems.

Used when the Fax button on the order screen phone definitions is clicked.

FO_LabInfo.CallToOrderCode

Used in the mini window for call/fax to automatically order a test code when the Call button is clicked on the order screen.

Enter a valid order code.

FO_LabInfo.CashFeeSchedule

Default fee schedule code applied to FAST accessions labeled as 'Bill to Cash'.

Enter a valid fee schedule code.

FO_LabInfo.CashFeeScheduleOption

Default fee schedule option applied to FAST accessions labeled as 'Bill to Cash'.

Enter a valid fee schedule option.

FO_LabInfo.CDC_In_Interfaces

Interface code for Client Data Concentrator inbound interface.

Code is written to the interface code field when a trigger row is written by FAST. It must match what is expected for interface to function.

FO_LabInfo.CDC_OUT_Cancel_Order_Control

Cancellation order control to be used in FO_IF_Trigger_CDCOutbound.

OrderControl when FAST writes a cancellation trigger.

Enter OC or CA

Code is written to the trigger table when a trigger row is written by FAST.

FO_LabInfo.CDC_Out_Interfaces

Interface code for Client Data Concentrator outbound interface.

Code is written to the interface code field when a trigger row is written by FAST. It must match what is expected for interface to function.

FO_LabInfo.CDCOrderEvalHours

Represents a number of hours.

Enter an integer for the number of hours.

Default is 0.

Used to validate the collection date/time on the order screen when a previously created order is opened.

If the order collection date/time is older than this value, the collection date/time field is cleared to allow the user to enter a new one.

FO_LabInfo.CID_Prefix

Prefix characters for ContainerID.

Enter the character string to use as the prefix for ContainerIDs.

FO_LabInfo.CollectionLocations

System-level default for collection location if not defined at the user level.

Enter a valid collection location.

Used to evaluate the collection location entered on the order screen.

FO_LabInfo.Def_AreaCode

System-level default for area code.

Enter an integer for a valid area code.

Used on the patient demographic screen if area code is not provided.

FO_LabInfo.Def_ClientCode

System-level default client ID code.

Enter a valid client ID code.

FO_LabInfo.Def_Epi_Days

Enter the integer 30

Do NOT change without Rhodes approval.

FO_LabInfo.Def_PtLocCode

System-level default patient location code on the order screen.

Enter a valid patient location code.

This code is only used if no value is in the field when the order is saved.

FO_LabInfo.DefaultBatchDestination

System-level default batch destination code.
Enter a valid batch destination code.
Used if not provided by rules for transport logic.

FO_LabInfo.DefaultFacilityID

System-level default facility ID code.
Enter a valid facility ID code.

FO_LabInfo.DefaultFeeSchedule

Default fee schedule for multiple fee schedule implementations.

FO_LabInfo.DefaultFeeScheduleOption

Default option in the default fee schedule for multiple fee schedule implementations.

FO_LabInfo.DefaultPerformingLab

System-level default performing lab code value.
Enter a valid performing lab code value.
Used to supply a performing lab code to the system when one is required and not provided by rules.

FO_LabInfo.DefaultSpeciesCode

Default species code.
H = HUMAN

FO_LabInfo.DefaultSpeciesName

Default species name corresponding to the default species code.
HUMAN

FO_LabInfo.DefaultWorkFlowMethod

System default workflow.
Overridden by a user location or user-defined default workflow.
Enter an allowed value.
Allowed values:

PATIENT PRESENTS
SPECIMEN PRESENTS
INDUSTRIAL TOX

FO_LabInfo.DefOrdScreenReq

System-level default requisition report name used when the REQ button on the order screen is clicked.
Default used when the user-level value is not defined.
Required value.
Use Rhodes recommended value.

FO_LabInfo.DispatchListRPTEExternalFormCode

The external form code for the dispatch list user custom report.

FO_LabInfo.DisplayBDEFields

Determines which fields to display in the blind duplicate entry screen.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter allowed values shown below separated by pipes.
The default value of |ALL| may be used to display all fields.
If this field is blank, the system will default to |ALL|.
Allowed values:
M = MRN
N = patient name
D = DOB
S = gender
T = telephone
C = client
L = location
P = physician
E = test related fields
CC1 = copy to 1
CC2 = copy to 2
CC3 = copy to 3
CC4 = copy to 4
ADD = address fields

FO_LabInfo.Epi_BillTo_Options

Populates Bill To option drop-down list on the Episode Definition screen.

Multidimensional pipe delimited value, with leading and trailing pipes.

Enter valid billto codes separated by pipes.

IE: |P|C||

FO_LabInfo.Epi_Ins_Options

Populates Insurance option drop-down list on the Episode Definition screen.

Multidimensional pipe delimited value, with leading and trailing pipes.

Enter valid insurance codes separated by pipes.

IE: |INS1|INS2|INS3|

FO_LabInfo.ExceptionExecFolder

Pathway for CSTools installation.

Enter a valid network path.

FO_LabInfo.ExceptionExecutable

File name for CSTools executable.

Include ".exe" in the file name.

FO_LabInfo.FastingOrderCode

Used to automatically order a test if the fasting priority is selected at the order level on the order screen. The rule is activated at the time the Verify button is clicked.

Enter a valid order test code.

FO_LabInfo.FaxToOrderCode

Used in the mini window for call/fax to automatically order a test code when the Fax button is clicked on the order screen.

Enter a valid order code.

FO_LabInfo.FPtoRREInterfaceCode

Interface code for the Fast to RRE interface service.

Enter a valid interface code.

FO_LabInfo.FutureOrderDays

Number of days in the future that the system will allow a user to date a new order.

Enter an integer for the number of days.

The collection date is evaluated and if the order is too far in the future, a warning message will be displayed.

FO_LabInfo.FutureOrderSecsAutoReceive

Represents a number of seconds.

Enter an integer for the number of seconds.

If the collection date/time is in the future by more than this number of seconds, the accession is excluded from auto receive processes.

FO_LabInfo.FutureOrderSecsNotTriggerLabels

Represents a number of seconds.

Enter an integer for the number of seconds.

If the collection date/time is in the future by more than this number of seconds, no label is produced.

FO_LabInfo.ITOXDeflCDCCodeq

Default diagnosis code for orders placed while in ITOX workflow.

Enter a valid diagnosis code.

FO_LabInfo.ITOXDefProviderCode

Default provider code for orders placed while in ITOX workflow.

Enter a valid provider code.

FO_LabInfo.LabAccessionAlphaCharacters

Represents the letters used in the lab accession generation when FAST will pre-generate it and send it to the LIS.

Multidimensional pipe delimited value, with leading and trailing pipes.

Enter single capital letters separated by pipes.

IE: |A|Q|Z|

FO_LabInfo.LabAccessionFormat

Defines format for creation of lab accession values.

Use Rhodes recommended value.

IE: 1A,8N

The format '1A,8N' generates lab accessions that are one alpha character followed by 8 numeric characters.

FO_LabInfo.LabAddress1

Address field on reports.

FO_LabInfo.LabAddress2

Second address field on reports.

FO_LabInfo.LabAddress3

Third address field on reports.

FO_LabInfo.LabAddress4

Fourth address field on reports.

FO_LabInfo.LabCode

Code value for this lab.

FO_LabInfo.LabDirector

Name of lab director on reports.

FO_LabInfo.LabDivisionCode

Connects a lab code to a larger organization charting process.

Enter a valid division code as defined in an organizations chart.

FO_LabInfo.LabInfo_ID

ID field, a counter. Unique

FO_LabInfo.LabName

Laboratory name for the login screen and reports.

FO_LabInfo.LabRegionCode

Connects a lab code to a larger organization charting process.
Enter a valid region code as defined in an organizations chart.

FO_LabInfo.LabSubDivisionCode

Connects a lab code to a larger organization charting process.
Enter a valid sub-division code as defined in an organizations chart.

FO_LabInfo.LogoImageFile

The network path and file name for the logo file used on screen and report displays.
Enter a valid network path and file name.
The file must be a GIF or JPG image approximately 100x125 pixels.

FO_LabInfo.MaxOrderCopyToProvs

Defines the maximum number of 'Copy To' providers allowed per order.
Enter an integer from 0 to 10.

FO_LabInfo.Misc1

Login screen user defined field #1.

FO_LabInfo.Misc2

Login screen user defined field #2.

FO_LabInfo.Misc3

Login screen user defined field #3.

FO_LabInfo.Misc4

Login screen user defined field #4.

FO_LabInfo.Misc5

Login screen user defined field #5.

FO_LabInfo.MRNumGenerationRoutine

Automatically generates an MRN number on the patient data screen.
Use Rhodes recommended value.
Typical value: ALPHA4NUMBER4

FO_LabInfo.MRNumMask

Medical record number mask used to validate the MRN field on the order screen.
Enter “#” to represent numbers and “@” to represent alpha characters.
Typical setting: @@@@#####

FO_LabInfo.OE_Interface

Default value for the Outbound OE system interface.
Use Rhodes recommended value.

FO_LabInfo.OrderActionPhoneNumbers

Designed for use in TEST area.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter phone numbers, separated by pipes, to limit user's choice of entry.

FO_LabInfo.OrderCollectLocationTypes

Populates the collection type drop-down on the patient collection location screen.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter valid collection type codes separated by pipes.

FO_LabInfo.PasswordExpirationDays

Number of days before a user password expires and must be reset.
Enter an integer for the number of days.

FO_LabInfo.PastOrderDays

Number of days back that the system will allow a user to date a new order.
Enter an integer for the number of days.
The collection date is evaluated and if the order is too old, a warning message will be displayed.

FO_LabInfo.PatientFeeSchedule

Default fee schedule code applied to FAST accessions labeled with a billto value of 'Patient/Guarantor'.
Enter a valid fee schedule code.

FO_LabInfo.PatientFeeScheduleOption

Default fee schedule option applied to FAST accessions labeled with a billto value of 'Patient/Guarantor'.
Enter a valid fee schedule option.

FO_LabInfo.PaymentCardTypes

Populates the credit type drop-down on the payment screen.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter valid credit card type codes separated by pipes.
IE: |AMEX|VISA|DINNERS|DEBIT|

FO_LabInfo.PaymentReceiptExternalFormCode

The form code from FO_External_Form_Definition.
ExternalFormCode that can be used to show a user-customized SSRS-based payment receipt form.

FO_LabInfo.PaymentTypes

Populates the payment type drop-down on the payment screen.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter valid payment type codes separated by pipes.
IE: |CARD|CHECK|CASH|

FO_LabInfo.ProvCodesTriggerFreeText

Defines provider codes for which a freetext provider name is allowed.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter valid provider codes separated by pipes.

FO_LabInfo.PtDefaultDOB

Default DOB.
Enter DOB as MM/DD/YYYY format.

FO_LabInfo.PtEthnicityEntries

Populates the ethnicity drop-down on the patient demographics screen.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter valid ethnicity codes separated by pipes.

FO_LabInfo.PtRaceEntries

Populates the race drop-down on the patient demographics screen.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter valid race codes separated by pipes.

FO_LabInfo.RecentPatientSearchDays

Default number of days to evaluate for recent activity.
Enter an integer for the number of days.
Used with RECENT PTS search option.
Based on edit date not create date.

FO_LabInfo.RecentPatientSearchType

Default RECENT PTS search type.
Enter an allowed value.
Allowed values:
USERLOCATION
ENTRYGROUPCODE
PTACCESSGROUP
MPI

FO_LabInfo.RecognizedPrefixes

Defines the prefixes to remove from patient last name in patient matching rules.
Storage of prefixes depends on permission.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter patient last name prefixes that should be removed from patient last names via matching rules.
Enter prefixes separated by pipes.

FO_LabInfo.RecognizedSuffixes

Defines the suffixes to remove from patient last name in patient matching rules.
Storage of suffixes depends on permission.

Multidimensional pipe delimited value, with leading and trailing pipes.
Enter patient last name suffixes that should be removed from patient last names via matching rules.
Enter suffixes separated by pipes.

FO_LabInfo.ReqID_Exclude_Characters

Defines the characters to exclude from the requisition ID value.
Multidimensional COMMA delimited value.
Enter the characters, separated by commas, that should be excluded from the requisition ID value on the order screen.

FO_LabInfo.ReqID_Length_Range

Represents the minimum and maximum number of characters allowed in the requisition ID field on the order screen.
Enter two integers separated by a dash.
Do not enter a value here if an edit mask is defined for the requisition ID field.
If the value is set as '10-15', then an entry between 10 and 15 characters long is allowed.

FO_LabInfo.ReqID_Mask

Mask used to validate the requisition ID on the order screen.
Enter “#” to represent numbers and “@” to represent alpha characters.
Typical setting: #####
This setting requires an 8 character numeric only entry.

FO_LabInfo.Result_Interface

Default value for the Outbound RE system interface.
Use Rhodes recommended value.

FO_LabInfo.ResultSysURL

URL to connect to a client-provided lab result portal.
Enter a valid URL.
The URL may contain place holders for user name and password for the client-provided lab system.
IE: HTTP://LabPortal.com /#USERNAME##PASSWORD#

FO_LabInfo.SalesTaxUserLoc

Defines the user locations and their corresponding sales tax to be used for price calculations on the payments screen.

Multidimensional pipe delimited value, with leading and trailing pipes.

Enter valid user location code - sales tax percent pairs separated pipes.

Each value in a pair is separated by a dash.

IE: |USERLOC1-6.5|USERLOC2-6|

FO_LabInfo.SendOrderForFPCancelToLIS

Bit flag to indicate if FAST should trigger a new order message before a cancel message when sending cancellation to LIS.

This would only be true for orders that have not been previously sent to the LIS or have originated in LIS.

The system will evaluate both of these conditions by checking to see if the IFTriggerUpdate field has been filled at the test level.

Enter 0 or 1

0 = do not trigger NW order before cancel

1 = trigger NW Order before sending cancel

FO_LabInfo.SO_Review_Days

System-level default number of days before a standing order expires and requires review.

Enter an integer for the number of days.

Used to calculate the number of days until standing order expiration.

IE: 180

FO_LabInfo.SpecimenPresentsDefTechCode

Default tech code for collection tech in the Specimen Presents mode.

Enter a valid tech code.

FO_LabInfo.TDC_In_Interfaces

Interface code for Trusted Data Concentrator inbound interface.

Code is written to the interface code field when a trigger row is written by FAST. It must match what is expected for interface to function.

FO_LabInfo.TDC_Out_Interfaces

Interface code for Trusted Data Concentrator outbound interface.

Code is written to the interface code field when a trigger row is written by FAST. It must match what is expected for interface to function.

FO_LabInfo.TestCompDupExcludeDept

Defines the department codes to exclude from the test overlap/duplication logic during order entry.

Multidimensional pipe delimited value, with leading and trailing pipes.

Enter valid department codes separated by pipes.

This value is used to exclude the list of department codes it represents from applying to the test overlap/duplication logic during order entry.

Any department codes in this list will not be evaluated for test overlap.

IE: |BB|MC|CY|PATH|

If this field is blank, the system will default to |MC|BB|CY| and will exclude those departments from test overlap/duplication logic.

FO_LabInfo.TestCompDupExcludeTests

Defines the order codes to exclude from the test overlap/duplication logic during order entry.

Multidimensional pipe delimited value, with leading and trailing pipes.

Enter valid order codes separated by pipes.

This value is used to exclude the list of order codes it represents from applying to the test overlap/duplication logic during order entry.

Any order codes in this list will not be evaluated for test overlap.

FO_LabInfo.TriggerCancelCDCOutbound

Bit flag to indicate if FAST should trigger cancellation messages to the outbound CDC interface for orders where FO_Accessions.Origin equals 'C' or 'T'.

Enter 0 or 1

0 = do not trigger cancellation messages to outbound CDC

1 = trigger cancellation messages to outbound CDC

FO_LabInfo.UnknownCollectDate

Date sent to LIS when Unknown Collection box is checked.

Enter collect date as MM/DD/YYYY format.

FO_LabInfo.UnknownCollectTime

Time sent to LIS when Unknown Collection box is checked.
Enter collect time as HH:MM 24-hour format.

FO_LabInfo.UseClientDrivenOrderScreen

Bit flag to indicate if client-driven order screen is default order screen.
Enter 0 or 1
0 = use original FAST order screen
1 = use client-driven order screen

FO_LabInfo.UseInterfaceTriggerService

Bit flag to indicate if FAST should enable FAST Interface Trigger Layer.
Used in conjunction with FAST Interface Trigger Process Service.
Enter 0 or 1
0 = do not use trigger layer (FAST will continue to write to trigger table)
1 = use FAST Interface Trigger Layer and FAST Interface Trigger Process Service (started configured and separately)
(A background service for creating application to interface subsystem triggers.
When this is set the application writes general triggers for the background job to process in the table FO_IF_AppTrigger_Queue.
The background job then creates the explicit table updates and the triggering to the FO_ID_Trigger table.)

FO_LabInfo.UseMandatorySteps

Enter the integer 1
Do NOT change without Rhodes approval.

FO_LabInfo.UseVerify

Enter the integer 1
Do NOT change without Rhodes approval.

FO_LabInfo.WorkFlowMethods

Workflow methods used by the site.
Populates the workflow method drop-down on the integrated search page.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter one or more allowed values separated by pipes.

Allowed values:
PATIENT PRESENTS
SPECIMEN PRESENTS
INDUSTRIAL TOX

ForceBillTo [FO_IF_Translations]

Defines the billto value for every order created by reference to this translation.
Enter a valid FAST billto value. See Bill To table for valid entries of long code.
Only applies to translation type I insurance for the first IN1 segment.
This will override what was sent in the message or a default value for this MPI qualifier.
This logic will be used only if the translation rules are activated to cause the system to translate the insurance code in the message.
An IN1 segment must have at least an insurance code and a policy number to qualify as a valid segment. If it does not, no translation will be applied.

ForeignValue [FO_IF_Translations]

Enter a value for this translation type in the external system.

FModule [FO_External_Form_Definition]

Swaps the default Rhodes format for the SSRS form defined.
Enter a valid FModule code to enable.
Valid FModule Code:
BATCHPROCESS

FPtoRREInterfaceCode [FO_LabInfo]

Interface code for the Fast to RRE interface service.
Enter a valid interface code.

FPValue [FO_IF_Translations]

Enter a value to translate to in FAST.
For type I insurance translations, if the FPValue is "**DNU**", then the system will not record any insurances from that message.
The system will still force the billto value if the above field is valued.
This is only honored for the primary insurance (first IN1) segment in a message.

FutureOrderDays [FO_LabInfo]

Number of days in the future that the system will allow a user to date a new order.

Enter an integer for the number of days.

The collection date is evaluated and if the order is too far in the future, a warning message will be displayed.

FutureOrderSecsAutoReceive [FO_LabInfo]

Represents a number of seconds.

Enter an integer for the number of seconds.

If the collection date/time is in the future by more than this number of seconds, the accession is excluded from auto receive processes.

FutureOrderSecsNotTriggerLabels [FO_LabInfo]

Represents a number of seconds.

Enter an integer for the number of seconds.

If the collection date/time is in the future by more than this number of seconds, no label is produced.

InterfaceCode [FO_IF_Translations]

Interface code for this translation. The interface code is defined in the Comms and Processor jobs config files.

ITOXDeflCDCCodeq [FO_LabInfo]

Default diagnosis code for orders placed while in ITOX workflow.

Enter a valid diagnosis code.

ITOXDefProviderCode [FO_LabInfo]

Default provider code for orders placed while in ITOX workflow.

Enter a valid provider code.

LabAccessionAlphaCharacters [FO_LabInfo]

Represents the letters used in the lab accession generation when FAST will pre-generate it and send it to the LIS.

Multidimensional pipe delimited value, with leading and trailing pipes.
Enter single capital letters separated by pipes.
IE: |A|Q|Z|

LabAccessionFormat [FO_LabInfo]

Defines format for creation of lab accession values.
Use Rhodes recommended value.
IE: 1A,8N
The format '1A,8N' generates lab accessions that are one alpha character followed by 8 numeric characters.

LabAddress1 [FO_LabInfo]

Address field on reports.

LabAddress2 [FO_LabInfo]

Second address field on reports.

LabAddress3 [FO_LabInfo]

Third address field on reports.

LabAddress4 [FO_LabInfo]

Fourth address field on reports.

LabCode [FO_LabInfo]

Code value for this lab.

LabDirector [FO_LabInfo]

Name of lab director on reports.

LabDivisionCode [FO_LabInfo]

Connects a lab code to a larger organization charting process.
Enter a valid division code as defined in an organizations chart.

LabInfo_ID [FO_LabInfo]

ID field, a counter. Unique

LabName [FO_LabInfo]

Laboratory name for the login screen and reports.

LabRegionCode [FO_LabInfo]

Connects a lab code to a larger organization charting process.
Enter a valid region code as defined in an organizations chart.

LabSubDivisionCode [FO_LabInfo]

Connects a lab code to a larger organization charting process.
Enter a valid sub-division code as defined in an organizations chart.

LogoImageFile [FO_LabInfo]

The network path and file name for the logo file used on screen and report displays.
Enter a valid network path and file name.
The file must be a GIF or JPG image approximately 100x125 pixels.

M

MaxOrderCopyToProvs [FO_LabInfo]

Defines the maximum number of 'Copy To' providers allowed per order.
Enter an integer from 0 to 10.

Misc1 [FO_LabInfo]

Login screen user defined field #1.

Misc2 [FO_LabInfo]

Login screen user defined field #2.

Misc3 [FO_LabInfo]

Login screen user defined field #3.

Misc4 [FO_LabInfo]

Login screen user defined field #4.

Misc5 [FO_LabInfo]

Login screen user defined field #5.

MPIQualifier [FO_CDC_Outbound_Filter]

Enter a valid MPI qualifier code that accepts inbound messages; use only MPI qualifiers that have inbound interfaces so FAST can send out a message.

To learn which MPI qualifier codes are valid here, look at FO_MPI_Qualifier.UseForCDCOutboundProcessing. If that field is set to 1, that MPI Qualifier code is valid to use here.

MPIQualifier [FO_IF_Translations]

MPI qualifier code.

Enter a valid MPI qualifier code.

MRNumGenerationRoutine [FO_LabInfo]

Automatically generates an MRN number on the patient data screen.

Use Rhodes recommended value.

Typical value: ALPHA4NUMBER4

MRNumMask [FO_LabInfo]

Medical record number mask used to validate the MRN field on the order screen.

Enter “#” to represent numbers and “@” to represent alpha characters.

Typical setting: @@@@#####

Multidimensional pipe delimited value

Method which allows entry of multiple values in a field.

Values are separated by the pipe character -- |

In addition a leading, or starting, and trailing, or ending pipe is required.

For example the string

|A|B|C|D|

provides the values A, B, C and D to the system.

O

OE_Interface [FO_LabInfo]

Default value for the Outbound OE system interface.

Use Rhodes recommended value.

OrderActionPhoneNumbers [FO_LabInfo]

Designed for use in TEST area.

Multidimensional pipe delimited value, with leading and trailing pipes.

Enter phone numbers, separated by pipes, to limit user's choice of entry.

OrderCollectLocationTypes [FO_LabInfo]

Populates the collection type drop-down on the patient collection location screen.

Multidimensional pipe delimited value, with leading and trailing pipes.

Enter valid collection type codes separated by pipes.

OrderControl [FO_CDC_Outbound_Filter]

Order control code used with SENDNA option.

P

PasswordExpirationDays [FO_LabInfo]

Number of days before a user password expires and must be reset.

Enter an integer for the number of days.

PastOrderDays [FO_LabInfo]

Number of days back that the system will allow a user to date a new order.

Enter an integer for the number of days.

The collection date is evaluated and if the order is too old, a warning message will be displayed.

PatientFeeSchedule [FO_LabInfo]

Default fee schedule code applied to FAST accessions labeled with a billto value of 'Patient/Guarantor'.
Enter a valid fee schedule code.

PatientFeeScheduleOption [FO_LabInfo]

Default fee schedule option applied to FAST accessions labeled with a billto value of 'Patient/Guarantor'.
Enter a valid fee schedule option.

PaymentCardTypes [FO_LabInfo]

Populates the credit type drop-down on the payment screen.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter valid credit card type codes separated by pipes.
IE: |AMEX|VISA|DINNERS|DEBIT|

PaymentReceiptExternalFormCode [FO_LabInfo]

The form code from FO_External_Form_Definition.
ExternalFormCode that can be used to show a user-customized SSRS-based payment receipt form.

PaymentTypes [FO_LabInfo]

Populates the payment type drop-down on the payment screen.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter valid payment type codes separated by pipes.
IE: |CARD|CHECK|CASH|

PermGroups [FO_External_Form_Definition]

Determines which users can see a report based on permission group codes.
Leave blank to make report available to all users.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter valid permission group codes separated by pipes.

ProvCodesTriggerFreeText [FO_LabInfo]

Defines provider codes for which a freetext provider name is allowed.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter valid provider codes separated by pipes.

PtDefaultDOB [FO_LabInfo]

Default DOB.
Enter DOB as MM/DD/YYYY format.

PtEthnicityEntries [FO_LabInfo]

Populates the ethnicity drop-down on the patient demographics screen.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter valid ethnicity codes separated by pipes.

PtRaceEntries [FO_LabInfo]

Populates the race drop-down on the patient demographics screen.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter valid race codes separated by pipes.

R

RecentPatientSearchDays [FO_LabInfo]

Default number of days to evaluate for recent activity.
Enter an integer for the number of days.
Used with RECENT PTS search option.
Based on edit date not create date.

RecentPatientSearchType [FO_LabInfo]

Default RECENT PTS search type.
Enter an allowed value.
Allowed values:
USERLOCATION
ENTRYGROUPCODE
PTACCESSGROUP
MPI

RecognizedPrefixes [FO_LabInfo]

Defines the prefixes to remove from patient last name in patient matching rules.
Storage of prefixes depends on permission.
Multidimensional pipe delimited value, with leading and trailing pipes.

Enter patient last name prefixes that should be removed from patient last names via matching rules.
Enter prefixes separated by pipes.

RecognizedSuffixes [FO_LabInfo]

Defines the suffixes to remove from patient last name in patient matching rules.
Storage of suffixes depends on permission.
Multidimensional pipe delimited value, with leading and trailing pipes.
Enter patient last name suffixes that should be removed from patient last names via matching rules.
Enter suffixes separated by pipes.

ReportType [FO_External_Form_Definition]

Code for the report type.
Enter a string to identify the type. This code may be used as the type for other reports also.

ReportURL [FO_External_Form_Definition]

URL that launches the report in the SSRS server.
Enter a valid URL.

ReqID_Exclude_Characters [FO_LabInfo]

Defines the characters to exclude from the requisition ID value.
Multidimensional COMMA delimited value.
Enter the characters, separated by commas, that should be excluded from the requisition ID value on the order screen.

ReqID_Length_Range [FO_LabInfo]

Represents the minimum and maximum number of characters allowed in the requisition ID field on the order screen.
Enter two integers separated by a dash.
Do not enter a value here if an edit mask is defined for the requisition ID field.
If the value is set as '10-15', then an entry between 10 and 15 characters long is allowed.

ReqID_Mask [FO_LabInfo]

Mask used to validate the requisition ID on the order screen.
Enter “#” to represent numbers and “@” to represent alpha characters.

Typical setting: #####

This setting requires an 8 character numeric only entry.

Result_Interface [FO_LabInfo]

Default value for the Outbound RE system interface.

Use Rhodes recommended value.

ResultSysURL [FO_LabInfo]

URL to connect to a client-provided lab result portal.

Enter a valid URL.

The URL may contain place holders for user name and password for the client-provided lab system.

IE: HTTP://LabPortal.com /#USERNAME##/PASSWORD#

S

SalesTaxUserLoc [FO_LabInfo]

Defines the user locations and their corresponding sales tax to be used for price calculations on the payments screen.

Multidimensional pipe delimited value, with leading and trailing pipes.

Enter valid user location code - sales tax percent pairs separated pipes.

Each value in a pair is separated by a dash.

IE: |USERLOC1-6.5|USERLOC2-6|

SendCancel [FO_CDC_Outbound_Filter]

Bit field to determine if cancel order messages are sent on CDCOutbound.

Enter 0 or 1

0 = filter cancel order messages, do not send

1 = send cancel order messages

SendNA [FO_CDC_Outbound_Filter]

Bit field to determine if SN/NA messages are sent on CDCOutbound.

Enter 0 or 1

0 = filter SN/NA messages, do not send

1 = send SN/NA messages

SendOrder [FO_CDC_Outbound_Filter]

Bit flag to determine if order messages are sent on CDCOutbound.

Enter 0 or 1

0 = filter order messages, do not send

1 = send order messages

SendOrderForFPCancelToLIS [FO_LabInfo]

Bit flag to indicate if FAST should trigger a new order message before a cancel message when sending cancellation to LIS.

This would only be true for orders that have not been previously sent to the LIS or have originated in LIS.

The system will evaluate both of these conditions by checking to see if the IFTtriggerUpdate field has been filled at the test level.

Enter 0 or 1

0 = do not trigger NW order before cancel

1 = trigger NW Order before sending cancel

SendReceipt [FO_CDC_Outbound_Filter]

Bit flag to determine if receipt order messages are sent on CDCOutbound.

Enter 0 or 1

0 = filter receipt order messages, do not send

1 = send receipt order messages

SO_Review_Days [FO_LabInfo]

System-level default number of days before a standing order expires and requires review.

Enter an integer for the number of days.

Used to calculate the number of days until standing order expiration.

IE: 180

SpecimenPresentsDefTechCode [FO_LabInfo]

Default tech code for collection tech in the Specimen Presents mode.

Enter a valid tech code.

T

TDC_In_Interfaces [FO_LabInfo]

Interface code for Trusted Data Concentrator inbound interface.

Code is written to the interface code field when a trigger row is written by FAST. It must match what is expected for interface to function.

TDC_Out_Interfaces [FO_LabInfo]

Interface code for Trusted Data Concentrator outbound interface.

Code is written to the interface code field when a trigger row is written by FAST. It must match what is expected for interface to function.

TestCompDupExcludeDept [FO_LabInfo]

Defines the department codes to exclude from the test overlap/duplication logic during order entry.

Multidimensional pipe delimited value, with leading and trailing pipes.

Enter valid department codes separated by pipes.

This value is used to exclude the list of department codes it represents from applying to the test overlap/duplication logic during order entry.

Any department codes in this list will not be evaluated for test overlap.

IE: |BB|MC|CY|PATH|

If this field is blank, the system will default to |MC|BB|CY| and will exclude those departments from test overlap/duplication logic.

TestCompDupExcludeTests [FO_LabInfo]

Defines the order codes to exclude from the test overlap/duplication logic during order entry.

Multidimensional pipe delimited value, with leading and trailing pipes.

Enter valid order codes separated by pipes.

This value is used to exclude the list of order codes it represents from applying to the test overlap/duplication logic during order entry.

Any order codes in this list will not be evaluated for test overlap.

TranslationType [FO_IF_Translations]

Single character that represents a translation type.

Allowed values:

I = insurance

P = provider

C = client
B = bill to
T = test code
L = patient location
G = gender
R = relationship value
S = species
PR = priority
M = marital

TriggerCancelCDCOutbound [FO_LabInfo]

Bit flag to indicate if FAST should trigger cancellation messages to the outbound CDC interface for orders where FO_Accessions.Origin equals 'C' or 'T'.

Enter 0 or 1

0 = do not trigger cancellation messages to outbound CDC

1 = trigger cancellation messages to outbound CDC

U

UnknownCollectDate [FO_LabInfo]

Date sent to LIS when Unknown Collection box is checked.

Enter collect date as MM/DD/YYYY format.

UnknownCollectTime [FO_LabInfo]

Time sent to LIS when Unknown Collection box is checked.

Enter collect time as HH:MM 24-hour format.

UseClientDrivenOrderScreen [FO_LabInfo]

Bit flag to indicate if client-driven order screen is default order screen.

Enter 0 or 1

0 = use original FAST order screen

1 = use client-driven order screen

UseInterfaceTriggerService [FO_LabInfo]

Bit flag to indicate if FAST should enable FAST Interface Trigger Layer.

Used in conjunction with FAST Interface Trigger Process Service.

Enter 0 or 1

0 = do not use trigger layer (FAST will continue to write to trigger table)

1 = use FAST Interface Trigger Layer and FAST Interface Trigger Process Service (started configured and separately)

(A background service for creating application to interface subsystem triggers.

When this is set the application writes general triggers for the background job to process in the table FO_IF_AppTrigger_Queue.

The background job then creates the explicit table updates and the triggering to the FO_ID_Trigger table.)

UseMandatorySteps [FO_LabInfo]

Enter the integer 1

Do NOT change without Rhodes approval.

UseVerify [FO_LabInfo]

Enter the integer 1

Do NOT change without Rhodes approval.

W

WorkflowMethods [FO_LabInfo]

Workflow methods used by the site.

Populates the workflow method drop-down on the integrated search page.

Multidimensional pipe delimited value, with leading and trailing pipes.

Enter one or more allowed values separated by pipes.

Allowed values:

PATIENT PRESENTS

SPECIMEN PRESENTS

INDUSTRIAL TOX